

# Product data sheet

## Higo connectors - Micro X

### Micro X female cable connector



Z205XM P 00 DS 1000

<https://www.staging.ac-solutions.be/en/product/z205xmp00ds1000>

## Specifications

### General Characteristics

|                    |                                    |
|--------------------|------------------------------------|
| Number of contacts | 2                                  |
| Connector shape    | Plug                               |
| Gender             | Female                             |
| Color              | Red                                |
| Upper temperature  | 80 °C                              |
| Lower temperature  | -25 °C                             |
| IP Protection      | IP67                               |
| Mating cycles      | 200 Times                          |
| Connector diameter | 5.5 mm                             |
| Fitting length     | 36 mm                              |
| Cable Length       | 1000 mm                            |
| Cable diameter     | 2.4 mm                             |
| Wire section       | 2 x 0,14 mm <sup>2</sup>           |
| Terminal type      | IP67                               |
| Remark             | Other cable length/type on request |

# Product data sheet

## Higo connectors - Micro X

### Micro X female cable connector



## Electrical Parameters

|                            |                   |
|----------------------------|-------------------|
| Rated current              | 2 A               |
| Rated voltage              | 48 V AC / 60 V DC |
| Max. insulation resistance | ?20 M?            |
| Max. contact resistance    | ?10 m?            |

## Material

|                     |                  |
|---------------------|------------------|
| Material jacket     | PVC              |
| Insulation wire     | FEP              |
| Material of contact | Copper Alloy     |
| Contact plating     | Gold over Nickel |