

# Product data sheet

## Higo connectoren - L1019A

### Female rear panel mount connector



L1019AM R 03 DQ 0300

<https://www.staging.ac-solutions.be/nl/product/l1019amr03dq0300>

## Specificaties

### General Characteristics

|                       |                                    |
|-----------------------|------------------------------------|
| Number of contacts    | 10 (3+7)                           |
| Connector shape       | Rear panel mount                   |
| Gender                | Female                             |
| Color                 | Silver                             |
| Upper temperature     | 80 °C                              |
| Lower temperature     | -25 °C                             |
| Protection degree     | IP67                               |
| Mating cycles (times) | 200 Times                          |
| Connector diameter    | 24 mm                              |
| Remark                | Other cable length/type on request |

# Product data sheet

## Higo connectoren - L1019A

### Female rear panel mount connector



### Electrical Parameters

|                                 |                   |
|---------------------------------|-------------------|
| Rated current                   | 30 / 2 A          |
| Rated voltage                   | 48 V AC / 60 V DC |
| Max. insulation resistance (M?) | ?20 M?            |
| Max. contact resistance (M?)    | ?10 m?            |

### Material

|                     |                  |
|---------------------|------------------|
| Material of contact | Phosphor Bronze  |
| Contact plating     | Gold over Nickel |